



Hercules H/P 4000

M+S Rated

Item #	Tire Size & Service Description	Load Range	Sidewall	UTOG	Rim Width (in)	Single Max Load	Single Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
T, S-Speed Rated											
02824	P215/70R14 96T	STD	RWL	440 A B	6.5	1554	44	25.76	8.66	10.5	22.0
02826	P225/70R14 98T	STD	RWL	440 A B	6.5	1675	44	26.27	8.92	10.5	24.0
02808	P185/60R14 82T	STD	BSW	440 A B	5.5	1047	44	22.80	7.15	10.5	16.0
02782	P235/60R14 96T	STD	RWL	440 A B	7.0	1565	44	25.06	9.11	10.5	23.0
02828	P215/70R15 97T	STD	RWL	440 A B	6.5	1620	44	26.71	8.71	10.5	23.0
02830	P225/70R15 100T	STD	RWL	440 A B	6.5	1753	44	27.37	9.10	10.5	26.0
02832	P235/70R15 102T	STD	RWL	440 A B	7.0	1896	44	27.90	9.46	10.5	27.0
02834	P255/70R15 108T	STD	RWL	440 A B	7.5	2183	44	28.95	10.40	10.5	32.0
02798	P215/65R15 95T	STD	RWL	440 A B	6.5	1510	44	26.00	8.38	10.5	23.0
02790	P235/60R15 98T	STD	RWL	440 A B	7.0	1642	44	26.11	9.15	10.5	25.0
02792	P245/60R15 100T	STD	RWL	440 A B	7.0	1753	44	26.55	9.47	10.5	26.0
02794	P255/60R15 102T	STD	RWL	440 A B	7.5	1885	44	27.01	10.24	10.5	28.0
02796	P275/60R15 107T	STD	RWL	440 A B	8.0	2149	44	28.06	10.70	10.5	30.0
02770	P295/50R15 105S	STD	RWL	440 A C	9.5	2061	35	26.80	12.22	10.5	32.0
02806	P235/55R16 96T	STD	BSW	440 A B	7.5	1565	44	26.15	9.65	10.5	24.0