



Hercules Trail Digger® M/T

M+S Rated

Item #	Tire Size & Service Description	Load Range	Sidewall	UTOG	Rim Width (in)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)	Stud Size (in)
01238	LT235/75R15/6 104/101Q	C	OWL	-	6.5	1985	50	1820	50	28.90	9.00	18.0	32.0	15
01204	3 0X9.50R15LT/6 104Q	C	OWL	-	7.5	1985	50	-	-	29.30	9.75	19.5	37.0	17
01202	31X10.50R15LT/6 109Q	C	OWL	-	8.5	2270	50	-	-	30.50	10.50	20.0	41.0	17
01206	33X12.50R15LT/6 108Q	C	OWL	-	10.0	2205	35	-	-	32.50	12.80	20.5	52.0	17
01219	LT235/85R16/10 120/116Q	E	BSW	-	6.5	3042	80	2778	80	31.81	9.30	18.0	44.0	15
*01263	LT225/75R16/10 115/112Q	E	OWL	-	6.0	2680	80	2470	80	29.53	8.70	17.5	43.0	15
01217	LT245/75R16/10 120/116Q	E	BSW	-	7.0	3042	80	2778	80	30.71	9.40	17.5	39.0	15
01218	LT265/75R16/10 123/120Q	E	OWL	-	7.5	3415	80	3085	80	32.01	10.10	18.5	49.0	15
01220	LT285/75R16/8 122/119Q	D	OWL	-	8.0	3305	65	3000	65	33.10	11.30	18.5	53.0	15
01221	LT315/75R16/8 121/118Q	D	OWL	-	8.5	3195	50	2910	50	34.76	12.50	20.0	63.0	17
*01260	LT245/70R17/10 119/116Q	E	BSW	-	7.0	3000	80	2755	80	30.70	9.60	18.0	47.0	15
01230	LT265/70R17/10 121/118Q	E	OWL	-	8.0	3195	80	2910	80	31.65	11.03	18.5	50.0	15
*01265	LT285/70R17/10 121/118Q	E	OWL	-	8.5	3195	80	2910	80	33.00	11.50	18.5	58.0	15
01228	33X12.50R17LT/8 114Q	D	OWL	-	10.0	2600	50	-	-	32.50	12.80	20.5	57.0	17
01226	35X12.50R17LT/8 119Q	D	OWL	-	10.0	3000	50	-	-	34.85	12.67	20.5	62.0	17
*01203	LT275/70R18/10 125/122Q	E	BSW	-	8.0	3640	80	3305	80	33.35	11.00	20.5	62.0	17
*01264	LT275/65R18/10 123/120Q	E	OWL	-	8.0	3415	80	3085	80	32.32	10.98	18.0	56.0	15
*01205	35X12.50R20LT/10 121Q	E	BSW	-	10.0	3195	65	-	-	34.66	12.50	20.5	71.0	17

*Denotes 3-Ply sizes